



RolliGO

High speed roll-up door

Fast, safe, **price sensitive**
Suitable for interior and exterior
Suitable for busy crowded

- **It is the standard high speed door**, designed in order to be a reliable product at low costs

- **Opening and closing speed**
0,8 m/sec (to meet current regulation) with new. Digital controlled motor.

- **Easy setting** with digital control panel with Multilanguage Display.

- **Flexible curtain** with large standard all width windows and reinforcement bars.

- **Safety photocells** or Active Light Curtain for a fully safe operation that avoid contact with curtain during door closing.

- **Structure, curtain and windows** can be customized to satisfy customers requirements and the characteristics of the installation site.

Main features for installation

- Easy setting with digital control panel with Multilanguage Display. Photocells or Active Light Curtain for a fully safe operation that avoid contact with curtain during door closing.
- Structure, curtain and windows can be customized to satisfy customers requirements and the characteristics of the installation site.
- Easy fitting with state of the art electronic control box to control and adjust every device and door operation.



RolliGO

Fast, safe, price sensitive. Suitable for interior and exterior, for busy crowded places

Main features and technical specifications

Structure	Standard Galvanized. Optional powder coated or Stainless Steel AISI 304
Dimension Clear Passage	4500 x H 4500
Opening Speed	0,8 m/sec
Closing Speed	0,8 m/sec
Wind Load	UNI EN 12-424 Class 1
Main supply	400 V AC three phase
Curtain	Polyester curtain extra strong 950 gr/sqm
	flame retardant.
	Reinforcement bars inside curtain pockets.
	One vision windows full width standard
	(additional windows as option).
	Special windows upon request.
Insulated curtain	Optional Insulated curtain 3mm thickness.
	Acoustic insulation average 17,5 db

	(noise spectrum 100-3150Hz).
	Thermal insulation 3,7K with condensate reduction.
Motor	Motor unit three phase single speed type 1KWatt Easy
	precabled with plugs, Digital Encoder.
Control Panel	Digital controller with Multilanguage Display for easy setting, speeds
	management, Open/Stop/Close buttons, 4 operating modes,
	Pedestrian opening and Passage Detection.
	Programmable output relais.
	Service management with historic events record.
Limit switch	Standard Digital Encoder (absolute encoder)
Safety	One pair of photocells.Optional flexible active bottom strip radio
	controller or Light Curtain. UNI EN12-453
Manual operation	Standard manual opening/closing with handle.
Certification	UNI EN 13241-1 Compliant



CURTAINS Standard available colours

									
RED Ral 3002	BLUE Ral 5010	ORANGE Ral 2004	LIGHT GREY RAL Ral 7035	MEDIUM GREY RAL Ral 7038	DARK GREY Ral 7037	CREAM Ral 1013	WHITE Ral 9003	SILVER Ral 9006	WHITE GREY Ral 9002
									
LIGHT BLUE Ral 5012	BLACK Ral 9005	ANTHRACITE Ral 7016	BLUE Ral 5015	BLUE Ral 5002	GREEN Ral 6005	GREEN Ral 6026	GREEN Ral 6018	YELLOW Ral 1003	YELLOW Ral 1021

